



109BF B - FLEXIBLE EPOXY B



SECTION 1: IDENTIFICATION

- 1.1 Product identifier:** 109BF B - FLEXIBLE EPOXY B
Other means of identification:
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses (Consumer use): Base for coatings
Relevant uses (Professional users): Base for coatings
Relevant uses (Industrial user): Base for coatings
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**
EPICOAT S.A. DE C.V.
2176 French Settlement rd Dallas, Texas 75212
Phone: 682 414 1623 Ein number 41 3045549
erod@theepicoats.com
<https://theepicoats.com/>
- 1.4 Emergency phone number:**

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
29 CFR 1910.1200:
Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200
Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302
Eye Dam. 1: Serious eye damage, Category 1, H318
Repr. 1B: Reproductive toxicity, Category 1B, H360
Skin Corr. 1B: Skin corrosion, Category 1B, H314
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

29 CFR 1910.1200:

Danger



Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed.
Repr. 1B: H360 - May damage fertility or the unborn child.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P264: Wash thoroughly after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of the contents/containers according to the local, state and federal regulations.

Substances that contribute to the classification

4-nonylphenol, branched; Bisphenol A

Additional labeling:



SECTION 2: HAZARD(S) IDENTIFICATION (continued)



WARNING

Federal Hazardous Substances Act (FHSA) >> Chronic toxicity (Reproductive Toxicants)
May damage fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Store locked up.

FIRST AID TREATMENT

If exposed or concerned: Get medical advice/attention.

Contains : 4-nonylphenol, branched; Bisphenol A.

This product can expose you to chemicals including Bisphenol A, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Federal Hazardous Substances Act (FHSA) >> Corrosive

Causes Burns. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Handle with care. Keep out of reach of children. Wear gloves and safety glasses. Use only in a well-ventilated area.

FIRST AID TREATMENT

If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

Contains : 4-nonylphenol, branched; Bisphenol A.

Federal Hazardous Substances Act (FHSA) >> Strong sensitizer (dermal)

May cause an allergic skin reaction. Wear gloves. Keep out of reach of children.

FIRST AID TREATMENT

If on skin, rinse well with water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Contains : 4-nonylphenol, branched; Bisphenol A.

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Mixture composed of additives and resins in solvents

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 84852-15-3	4-nonylphenol, branched Acute Tox. 4: H302; Flam. Liq. 4: H227; Repr. 2: H361; Skin Corr. 1B: H314 - Danger	50 - <75%
CAS: 80-05-7	Bisphenol A Eye Dam. 1: H318; Repr. 1B: H360; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	10 - <25%
CAS: Non-applicable	Aliphatic amine derivative Eye Irrit. 2A: H319; Skin Irrit. 2: H315 - Warning	10 - <25%

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:



SECTION 4: FIRST-AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:



109BF B - FLEXIBLE EPOXY B



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

8.2 Appropriate engineering controls:


A.- Individual protection measures, such as personal protective equipment




SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

40 CFR Part 59 (VOC):

V.O.C.(weight-percent):	0 % weight
V.O.C. at 68 °F:	0 kg/m ³ (0 g/L)



109BF B - FLEXIBLE EPOXY B



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F: Liquid
Appearance: Fluid
Color: Colorless
Odor: Aminic
Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: Non-applicable *
Vapour pressure at 68 °F: Non-applicable *
Vapour pressure at 122 °F: <300000 Pa (300 kPa)
Evaporation rate at 68 °F: Non-applicable *

Product description:

Density at 68 °F: 1001.3 kg/m³
Relative density at 68 °F: 0.87
Dynamic viscosity at 68 °F: 2616.1 mPa·s
Kinematic viscosity at 68 °F: 2612.61 mm²/s
Kinematic viscosity at 104 °F: Non-applicable *
Concentration: Non-applicable *
pH: Non-applicable *
Vapour density at 68 °F: Non-applicable *
Partition coefficient n-octanol/water 68 °F: Non-applicable *
Solubility in water at 68 °F: Non-applicable *
Solubility properties: Non-applicable *
Decomposition temperature: Non-applicable *
Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: Non Flammable (>199.4 °F)
Flammability (solid, gas): Non-applicable *
Autoignition temperature: 702 °F
Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Particle characteristics:

Median equivalent diameter: Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

Corrosive to metals: Non-applicable *

Heat of combustion: Non-applicable *

Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 68 °F: Non-applicable *

Refraction index: Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: May damage fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
4-nonylphenol, branched CAS: 84852-15-3	LD50 oral	1412 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
Bisphenol A CAS: 80-05-7	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	3000 mg/kg	Rabbit
	LC50 inhalation dust		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
4-nonylphenol, branched CAS: 84852-15-3	LC50	0.05 mg/L (96 h)	Acipenser oxyrhynchus
	EC50	0.14 mg/L (48 h)	Daphnia magna
	EC50	1.3 mg/L (72 h)	Scenedesmus subspicatus
Bisphenol A CAS: 80-05-7	LC50	4.6 mg/L (96 h)	Pimephales promelas
	EC50	3.8 mg/L (48 h)	Daphnia magna
	EC50	Non-applicable	

Chronic toxicity:

Identification	Concentration	Species	Genus
4-nonylphenol, branched CAS: 84852-15-3	NOEC	0.006 mg/L	Oncorhynchus mykiss
	NOEC	0.024 mg/L	Daphnia magna
Bisphenol A CAS: 80-05-7	NOEC	>0.01 - 0.1 mg/L	Fish
	NOEC	>0.01 - 0.1 mg/L	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability	Biodegradability
Bisphenol A CAS: 80-05-7	BOD5	Non-applicable
	COD	Non-applicable
	BOD5/COD	Non-applicable
	Concentration	100 mg/L
	Period	14 days
	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential
4-nonylphenol, branched CAS: 84852-15-3	BCF
	Pow Log
	Potential
Bisphenol A CAS: 80-05-7	BCF
	Pow Log
	Potential

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
4-nonylphenol, branched CAS: 84852-15-3	Koc	22000	Henry	11.02 PaΣm³/mol
	Conclusion	Immobile	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Bisphenol A CAS: 80-05-7	Koc	796	Henry	1.013E-6 PaΣm³/mol
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	3.76E-3 N/m (687.97 °F)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):



109BF B - FLEXIBLE EPOXY B



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** UN3066
14.2 UN proper shipping name: PAINT RELATED MATERIAL
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group, if applicable: II
14.5 Marine pollutant: Yes
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number:** UN3066
14.2 UN proper shipping name: PAINT RELATED MATERIAL
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group, if applicable: II
14.5 Marine pollutant: Yes
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Special regulations: 163, 367
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: Non-applicable
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN3066
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group, if applicable:** II
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *4-nonylphenol, branched (84852-15-3)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *Bisphenol A (80-05-7)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Non-applicable
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK - Substance List: *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*
- Minnesota - Hazardous substances ERTK: Non-applicable
- New Jersey Worker and Community Right-to-Know Act: *Bisphenol A (80-05-7)*
- New York RTK - Substance list: *Bisphenol A (80-05-7)*
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: Non-applicable
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*
- Rhode Island - Hazardous substances RTK: Non-applicable
- SB-258 Cleaning Product Right to Know Act : *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*
- The Toxic Substances Control Act (TSCA) : *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *4-nonylphenol, branched (84852-15-3)* ; *Bisphenol A (80-05-7)*

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

- H314: Causes severe skin burns and eye damage.
- H318: Causes serious eye damage.
- H360: May damage fertility or the unborn child.
- H317: May cause an allergic skin reaction.
- H335: May cause respiratory irritation.
- H302: Harmful if swallowed.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3



SECTION 16: OTHER INFORMATION (continued)

29 CFR 1910.1200:

Acute Tox. 4: H302 - Harmful if swallowed.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Flam. Liq. 4: H227 - Combustible liquid.

Repr. 1B: H360 - May damage fertility or the unborn child.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET